


ModuleX[®]

North American Product Guide Book Vol.2

September 2018

North American Product guide book vol.2



Corporate message

The light of refined emotion

Light is not just a medium that provides brightness.
What we aim to produce with our lighting are feelings
and irreplaceable experience.

Our proud lighting comes with “functions”
that can increase the value of space and environment and “effects”
that bring about comfort and sophistication.
Ordinary light cannot raise the value of space nor cause warm feelings among people.

What is “LIGHTING?”

It is an “Integrated Lighting Solutions” generated by combining
“hardware technology (equipment technology)” and
“software technique (lighting design)” that serve the needs of each individual client.
We “ModuleX”, continue our endeavor to advance
as lighting professionals and be a pioneer of innovative lighting solutions to provide
“Integrated Lighting Solutions” as our brand “ModuleX”.

From all staff and directors
ModuleX Inc.




“LIGHTING” the key to unite people and their environment

Ordinary light is just an electrical device. But ,“LIGHTING” is different. We consider “LIGHTING” as one of the most essential elements that combines people’s activities in particular buildings or space in a given area and environment.

The light has a big impact on the shaping of buildings, rooms and space. It also affects the sense of time and seasons as well as psychological comfort such as calmness and liveliness.

The light is directly linked to people’s mental state, the laws of nature and a long history of civilization and cultural development. We believe that the lighting equipment and design should take all these factors into consideration.



However, the recent lighting equipment seems to solely emphasize its data and statistics such as brightness, color rendering index and myopic ideas of energy -saving effect. An overflow of such information has neglected the key question of “how the light should exist in a particular place, time and environment.”

Easy-to-use materials for professionals must consistently come with simple yet versatile lighting functions and variations, technology to flexibly adjust own products and made-to-order options to accommodate clients’ needs, optical technology and lighting design that optimize the performance of such hardware, and fine-tuning support at each client’s site. We take pride in our products and services, and are determined to provide the best for your needs.

We look forward to serving you with
ModuleX’s Integrated Lighting Solutions.




ModuleX[®]

Integrated Lighting Solutions

ModuleX does not simply sell lighting fixtures.

With a wide variety of lighting effects and controlled light which only our original optical technology is able to produce, ModuleX is able to propose solutions which make up comfortable and always revitalizing space in accordance with each individual customer's project situations. This is what we call ModuleX Integrated Lighting Solutions.

ModuleX comes up with lighting plans/effects by conducting lighting environmental analysis and lighting simulations for each project.



ModuleX[®]

Hardware technologies

Elements
Lighting
functionality
system


Modularity
Adaptability to
fit any space

Optics
Unique optical
design

Light brushes for professionals

Bright, small and inconspicuous. These are what ModuleX considers to be the basic requirements for functional lighting fixtures. We believe, from a space and environmental designer's perspective, that the ideal state for lighting equipment required to illuminate objects in the target space is to have a minimal presence to be as inconspicuous as possible. At ModuleX, we continue to pursue this ideal state in our own unique way, with the latest revolutionary techniques and technologies.

At ModuleX, we do not work simply in pursuit of performance data for our catalogs. Our way of thinking with regard to lighting fixture design is to reflect and incorporate the points that are most important to professionals—such as the quality of light gradation, the range of adaptability and adjustability offered when using our products in the actual workplace, and the level of convenience when selecting which lighting fixtures to use—into our designs, and translate them into reality.



ModuleX[®] 60

DESIGN | MANUFACTURER
ModuleX.Inc
Tokyo, Japan



GOOD DESIGN
AWARD 2017
BEST 100



GOOD DESIGN AWARD 2017
Design of Production Development
GOOD DESIGN AWARD 2017
My Favorite Design

ModuleX classifies the functionality of stage lighting techniques.

These are the functions of lighting which derive from stage lighting technique to touch the right chord. With an application of stage lighting techniques, ModuleX lighting is precisely defined depending on its roles.

Ambient

Ambient beautifully balances the lighting, giving a final touch to the lighting design. It adjusts an overall balance by making subtle correction to the uneven luminosity on horizontal surfaces.



WALL

WALL is the light emitted on vertical surfaces that enter people's sight the most. Smooth and beautiful gradation and high diffusibility are required in order to enhance the depth and expanse of the space.




Accent

Accent is the light that highlights certain objects. Clear contrast and accurate directional light distribution are required to draw attention to a specific point.




Lighting system elements | Downlight

ModuleX lighting fixtures have a modular structure that enables separation of the lighting fixtures themselves from their mounting devices. This enables lighting effects to be changed after installation, even in the case of ceiling-embedded lighting fixtures.










Lighting system elements | Track light

The expression of basic lighting effects is constant, even when installed in a lighting duct. The lighting effects remain constant regardless of the installation method used.



Lighting system elements | GRID

The same principle applies with our GRID platform. Conformity and efficiency can be improved by re-considering the balance of lighting effects even in a space where having the bright light is good enough.




ModuleX systematizes our products by its functions to handle any requests from clients.

We are capable of presenting the proposal which actualizes the desired lighting effects/efficiency and economical efficiency regardless of different environment. In other words, our platform is able to add the value to our client projects.

Different functions/effects of light can be chosen in one size.

One of our major characteristics is that all types of fixtures are available in every size. This means that regardless of the space size, ModuleX can offer the same functions/effects of light.

ModuleX® 60	ModuleX® 80	ModuleX® 100	ModuleX® 130
$\phi 2\frac{7}{16}"$ $\phi 62\text{ mm}$	$\phi 3\frac{15}{64}"$ $\phi 82\text{ mm}$	$\phi 3\frac{15}{16}"$ $\phi 100\text{ mm}$	$\phi 5\frac{1}{8}"$ $\phi 130\text{ mm}$
			
			
			

ModuleX continues to pursue the minimization of the fixtures.

To elevate the value of space, minimizing the presence of the fixture itself is crucial for functional lighting fixtures. For brighter and greater light quality, we continue to develop our original optical technology and heat control technology to make our fixtures smaller, brighter and glare-controlled.

ModuleX Product Classification and Design Philosophy

1

ModuleX flagship platform to be particular about essential light quality

The flagship platform for interior and architecture

MUSEUM



The Basic Design in which the latest technology can be mounted. Particular about glare-control, the capability for adaptation and the essential quality of light.

2

Adapting the optical design to minimize the quantity of necessary fixtures while keeping the same lighting effects

Utility platform for interior and architecture

SLEEK



Unique optical technology ensures the comfort with a small number of lighting devices.

3

Establishing Both Lighting Effects and High Energy Efficiency

Tetragonal platform for interior and architecture

GRID




New lighting approach available because of LED technology in pursuit of technologies enabling an even distribution and application of light quality.

4


Always Same Lighting Effects for Indoor and Outdoor Fixtures

Outdoor platform for outdoor and landscape

MODS



Aiming to produce outdoor lighting devices that blend in with nature and the surrounding environment, and allow people to unconsciously find comfort in natural harmony.



Accent

The flagship platform
for interior and architecture

MUSEUM

Rather than simply cutting down glare, ModuleX optical design incorporates optical control down to the actual cone and enables various changes in light quality while minimizing the presence of the lighting fixture itself.



ModuleX optical reflector
LED is positioned in the deepest part of this special component. The reflector is optically curved by using our unique design and the development based on a definite integral method.

ModuleX Filter lighting[®]
You can change the type of lighting even after the installation is complete. Unlike some diffusion filters that immensely decrease the efficiency of devices or fresnel lenses that seep out or refract light and change the color of light, our lenses are designed with complex mechanisms and precision. In order to minimize the loss of device's efficiency after setting a filter, we adopted new materials and technology and have developed ultrathin precision lens filters.



Semi diffuser lens filter Full diffuser lens filter Semi spread lens filter Full spread lens filter Edge control lens filter Sharpener lens filter

ModuleX optical cone
An optical cone is an optical functional component that controls glare and irregular reflection from its inner surface according to the purpose of the product installation site.



CC : Chrome cone MC : Matte black cone WC : White cone

Minimizing the existence of fixtures by controlling the luminance with the precise control of reflection

Having the lowest light reflection to lower the luminance from all angles

Creating the sense of brightness in space Having the same brightness from any angles thanks to our original optical design

Angle index and pan lock · tilt lock mechanism
You can precisely check the lighting effects and fix the device firmly.
Tilt angle: 35 degrees




©Nacasa & Partners Inc.
ModuleX Global head office



©Nacasa & Partners Inc.
Harbor terrace Sasebo Geihinkan



©Nacasa & Partners Inc.
The Ritz Carlton Tokyo 'HINOKIZAKA'



Accent

The flagship platform
for interior and architecture

MUSEUM

The basic principle behind our spotlights is to control the lighting effects via the hood. Using our own uniquely designed optical reflectors enables us to achieve free and unfettered manipulation of lighting effects without producing unwanted glare.



ModuleX optical reflector
LED is positioned in the deepest part of this special component. The reflector is optically curved by using our unique design and the development based on a definite integral method.

ModuleX Filter lighting[®]
You can change the type of lighting even after the installation is complete. Unlike some diffusion filters that immensely decrease the efficiency of devices or fresnel lenses that seep out or refract light and change the color of light, our lenses are designed with complex mechanisms and precision. In order to minimize the loss of device's efficiency after setting a filter, we adopted new materials and technology and have developed ultrathin precision lens filters.



Semi diffuser lens filter Full diffuser lens filter Semi spread lens filter Full spread lens filter Edge control lens filter Sharpener lens filter

ModuleX optical hood
Our high-performance optical reflector keeps the reduction of illumination at the center to a minimal level even after a hood is installed. An optical baffle with pre-calculated shape and angle is situated inside the hood to reduce the glare. Up to two filters can be fitted in this component. (The actual product is fixed with fall prevention wires.)

Body color ※ModuleX color fitting : customized color can be ordered.




W: White S: Silver M: Matte Black

Adapting the major white color (specified in JPMA)

The silver color which can be merged into the surroundings

The most non reflecting color to diminish the existence of fixtures



Image



Aesop



Ambient

The flagship platform
for interior and architecture

MUSEUM

Our foundation lighting achieves a high level of glare-free, inconspicuousness and highly-uniform illumination over a wide area with beautiful light gradation through high-level optical control technology.

ModuleX optical reflector

Our optical reflectors offer both high energy efficiency and beautiful gradation, achieved through the development of a new light-distribution control method for the SSL (Solid State Lighting) era.

Module design

Even when using ceiling-suspended spotlights, ModuleX's modular design enables lighting spaces to be composed using the same kinds of lighting elements as with downlights.

ModuleX optical cone

An optical cone is an optical functional component that controls glare and irregular reflection from its inner surface according to the purpose of the product installation site.



CC : Chrome cone
Minimizing the existence of fixtures by controlling the luminance with the precise control of reflection



MC : Matte black cone
Having the lowest light reflection to lower the luminance from all angles



WC : White cone
Creating the sense of brightness in space
Having the same brightness from any angles thanks to our original optical design




©Nacasa & Partners Inc.
ModuleX Global head office



Nakayama Ophthalmology



©Nacasa & Partners Inc.
ModuleX Global head office



WALL

The flagship platform
for interior and architecture

MUSEUM

In order to create space with a sense of depth, it is necessary to illuminate the entire vertical plane with high-uniformity lighting. ModuleX's Wallwasher lighting fixtures illuminate the entire wall surface evenly, from the inside corners of the ceiling right down to the floor.

ModuleX optical reflector

ModuleX's wall lighting fixtures use a composite design combining reflectors and lens filters, and our own unique optical technology to achieve highly uniform light-distribution control in both the vertical and horizontal directions.

Module design

Even when using ceiling-suspended spotlights, ModuleX's modular design enables lighting spaces to be composed using the same kinds of lighting elements as with downlights. For example, it is possible to render a vertical plane by utilizing edge control or spread lens filters, installed inside a slanted hood-type fixture.

ModuleX optical cone

ModuleX's optical cones allow our wall lighting fixtures achieve even illumination to the inside corners of the ceiling, while at the same time producing a smooth gradation of light extending down towards the floor.




Beauty tune Shiseido



Kogakuin University



Waseda University Senior and Junior High School



ModuleX continues to pursue its own unique optical technologies, with the aim of creating “optical brushes” for lighting professionals.


The flagship platform for interior and architecture *MUSEUM*

ModuleX Filter lighting[®]

Sharpeners lens filter	Semi-diffuser lens filter	Full-diffuser lens filter	Semi-spread lens filter	Full-spread lens filter	Edge control lens filter
Controls the scope of illumination to create a contoured, condensed spotlight image. PAT.P D.PAT in Japan	Creates a soft, gentle gradation while retaining the core spotlight effect. PAT.P D.PAT in Japan	Creates a soft, wrap-around lighting effect similar to the effect produced by a reflector lamp.	Produces an easy-to-use short rectangle shape. (horizontal to vertical ratio: approx. 1: 2.8)	Produces a sharp, long rectangle shape. (horizontal to vertical ratio: approx. 1: 3.9) PAT.P in Japan	Adjusts the manner in which the light illuminates the wall surface, with a beautiful gradation effect. PAT.P D.PAT in Japan

Narrow reflector	10° hood						
	30° hood						
	50° hood						
Medium reflector	10° hood						
	30° hood						
	50° hood						

Downlight



Basic Model Number Specification Description
(Please specify for all cases)

MMP-080A/CC/SWF/N/10B 30/Z1/2

1 Platform

MMP	MUSEUM
ModuleX MUSEUM Platform	

2 Series

060	ModuleX® 60	size of hole for installation φ62mm φ 2 7/16"
080	ModuleX® 80	size of hole for installation φ82mm φ 3 15/64"
100	ModuleX® 100	size of hole for installation φ100mm φ 3 15/16"
130	ModuleX® 130	size of hole for installation φ130mm φ 5 1/8"
150	ModuleX® 150	size of hole for installation φ150mm φ 5 29/32"

3 Function

F	Ambient
W	Wall
A	Accent

4 Cone color

WC		White cone
MC		Matte black cone
CC		Chrome cone

5 Frame color

SWF		Single frame white
SMF		Single frame matte black

6 Light Distribution

N	Narrow
M	Medium
W	Wide
F	Flood
0 (zero)	Wall

7 Light Source

8 Color Temperature

24		2400K
27		2700K
30		3000K
35		3500K
40		4000K


9 Driver type

T_	Phase control type
Z_	0-10V

10 Authentication

1	PSE
2	CUL

Track light



Basic Model Number Specification Description
(Please specify for all cases)

MMP-080S/3H/S /1N/N/10B30/N1/2

1 Platform

MMP	MUSEUM
ModuleX MUSEUM Platform	

2 Series

060	ModuleX® 60
080	ModuleX® 80
100	ModuleX® 100
130	ModuleX® 130
150	ModuleX® 150

3 Function

S	Spotlight
---	-----------

4 Hood type

1H		Glare cut off angle 10° hood
3H		Glare cut off angle 30° hood
5H		Glare cut off angle 50° hood
SH		Slant hood

5 Color

W		White
M		Matte black
S		Silver

6 Plug type

1E	EUTRAC®	1 circuit
2E	EUTRAC®	2 circuit
1N	NORDIC®	1 circuit

7 Light Distribution

N	Narrow
M	Medium
W	Wide
F	Flood
0 (zero)	Wall

8 Light Source

It stands for classification and version of light source.
Depending on light source, it will change.

9 Color Temperature

24		2400K
27		2700K
30		3000K
35		3500K
40		4000K

10 Driver type


Z_	0-10V
N_	Non-dimming

11 Authentication

2	CUL
---	-----



U-B9451D/1/R27B/NC/W



1 Size

B9	ModuleX 100
----	-------------

2 Function

4	Wall
---	------

3 Light source

5X	LED(COB)
----	----------

4 Driver type

1	0-10V
2	EcoSystem type

5 Color Temperature

R27B		2700K
R30B		3000K
R35B		3500K
R40B		4000K

6 Cone color

WC		White cone
MC		Matte black cone
NC		Chrome cone

7 Frame color

SWF		Single frame white
SMF		Single frame matte black

▲ AMBIENT | Ambient downlight

MMP-060F

c

UL

US



Products Specifications

- Input Voltage

AC120 ~ 277V
- Power consumption

21.7W(AC120V) / 22.2W(AC277V)
- Luminance flux

1,536 ~ 1,857lm
- Color rendering

CRI (Ra)=93(typ)
- Fixture's weight

1.21lbs
- Light distribution

Flood (60°) Wide(48°) Medium (34°)
- Input current


0.5A
- Aiming distance

0.2m (7 7/8in)
- Ceiling thickness


23/64 ~ 63/64in
- Glare cut off angle

30°

Size



Installation



Product code

[ex : Chrome cone /White trim / Flood 60° / 3000K]
MMP-060F/CC/SWF/F/10A 30/T1/ 2


Basic Product Series	Cone color	Trim color	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------------	------------	--------------------	--------------	-------------------	-------------	-------------------

©Dimming | Phase control | 10-100%

White	MMP-060F/WC/SWF/F.W.M/ 10A24.27.30.35.40/T1/2
Matte black	MMP-060F/MC/SWF.SMF/F.W.M/ 10A24.27.30.35.40/T1/2
Chrome	MMP-060F/CC/SWF.SMF/F.W.M/ 10A24.27.30.35.40/T1/2


Light distribution (Chrome cone)

Flood : 60°




3000K / 1783Lm

Wide : 48°



3000K / 1783Lm

Medium : 34°



3000K / 1783Lm

MMP-060A



Product code

[ex : Chrome cone /White trim / Narrow 11° / 3000K]

MMP-060A/CC/SWF/N/10A 30/T1/ 2

Basic Product Series	Cone color	Trim color	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------------	------------	--------------------	--------------	-------------------	-------------	-------------------


©Dimming | Phase control | 10-100%

White	MMP-060A/WC/SWF/N.M/ 10A24.27.30.35.40/T1/2
Matte black	MMP-060A/MC/SWF.SMF/N.M/ 10A24.27.30.35.40/T1/2
Chrome	MMP-060A/CC/SWF.SMF/N.M/ 10A24.27.30.35.40/T1/2


Products Specifications

• Input Voltage	AC120 ~ 277V
• Power consumption	13.5W(AC120V) / 14.9W(AC277V)
• Luminance flux	941 ~ 1,088 lm
• Color rendering	CRI (Ra)=93(typ)
• Fixture's weight	1.19 lbs
• Light distribution	Narrow (11°) Medium (20°)
• Input current	0.35A
• Aiming distance	0.2m (7 7/8in)
• Ceiling thickness	23/64 ~ 63/64 in
• Tilting angle	35°
• Filter lighting®	2 Filters

Size



Installation



Additional Accesaries

• Lens Filter

Full-Diffuser lens filter
MLA-060/DF01



Semi-Diffuser lens filter
MLA-060/DS01



Full-spread lens filter
MLA-060/SF01



Semi-Spread lens filter
MLA-060/SS01




Edge-control lens filter
MLA-060/EC01



Sharpener lens filter
MLA-060/SH01




How to do tilt lock




Light distribution (for Chrome cone)

Narrow : 11°




Medium : 20°




Light distribution (for Chrome cone) with Filter lighting®




Full-Diffuser lens filter | MLA-060/DF01




Semi-Diffuser lens filter | MLA-060/DS01




Full-spread lens filter | MLA-060/SF01




Semi-Spread lens filter | MLA-060/SS01




Edge-control lens filter | MLA-060/EC01



Sharpener lens filter | MLA-060/SH01



The attachment of the filters



ACCENT | Track light


MMP-060S/1H



Products Specifications

- Input Voltage AC120V
- Power consumption 15.4W(AC120V)
- Luminance flux 941 ~ 1,088 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 0.82 lbs
- Light distribution Narrow (11°) Medium (19°)
- Input current 0.129A (120V)
- Aiming distance 0.1m (3 15/16 in)
- Tilting angle 100°
- Filter lighting® 2 Filters

Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA

NORDIC : type TEK-44,48,412
NORDIC ALUMINIUM INC

- This fixture is compatible with 2-circuit track only.
The fixture attaches to both the left and right circuit rails of the track.
Please ensure that only one power feed is supplied to the track.

Installation



Product code

[ex : 10°Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-060S/1H/W/1E/N/10A 30/Z1/ 2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth- entication
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	---------------------

©EUTRAC type

Dimming | 0-10V | 3-100%

White MMP-060S/1H/W/1E/N.M/10A24.27.30.35.40/Z1/2

Matte black MMP-060S/1H/M/1E/N.M/10A24.27.30.35.40/Z1/2

Chrome MMP-060S/1H/S/1E/N.M/10A24.27.30.35.40/Z1/2

©NORDIC type

Dimming | Non-dimming

White MMP-060S/1H/W/1N/N.M/10A24.27.30.35.40/N1/2

Matte black MMP-060S/1H/M/1N/N.M/10A24.27.30.35.40/N1/2

Chrome MMP-060S/1H/S/1N/N.M/10A24.27.30.35.40/N1/2

Additional Accesaries

• Lens Filter


Full-Diffuser lens filter
MLA-060/DF01



Semi-Diffuser lens filter
MLA-060/DS01



Full-spread lens filter
MLA-060/SF01



Semi-Spread lens filter
MLA-060/SS01



Edge-control lens filter
MLA-060/EC01




Sharpener lens filter
MLA-060/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°




Medium : 19°




Light distribution with Filter lighting®


Full-Diffuser lens filter | MLA-060/DF01




Semi-Diffuser lens filter | MLA-060/DS01




Full-spread lens filter | MLA-060/SF01




Semi-Spread lens filter | MLA-060/SS01




Edge-control lens filter | MLA-060/EC01



Sharpene lens filter | MLA-060/SH01



The attachment of the filters



ACCENT | Track light


MMP-060S/3H



Products Specifications

- Input Voltage AC120V
- Power consumption 15.4W(AC120V)
- Luminance flux 941 ~ 1,088 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 0.84 lbs
- Light distribution Narrow (11°) Medium (19°)
- Input current 0.129A (120V)
- Aiming distance 0.1m (3 15/16 in)
- Tilting angle 100°
- Filter lighting® 2 Filters

Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA

NORDIC : type TEK-44,48,412
NORDIC ALUMINIUM INC

- This fixture is compatible with 2-circuit track only.
The fixture attaches to both the left and right circuit rails of the track.
Please ensure that only one power feed is supplied to the track.

Installation



Product code

[ex : 30°Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-060S/3H/W/1E/N/10A 30/Z1/ 2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth- entication
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	---------------------

©EUTRAC type

Dimming | 0-10V | 3-100%

White	MMP-060S/3H/W/1E/N.M/10A24.27.30.35.40/Z1/2
Matte black	MMP-060S/3H/M/1E/N.M/10A24.27.30.35.40/Z1/2
Chrome	MMP-060S/3H/S/1E/N.M/10A24.27.30.35.40/Z1/2

©NORDIC type

Dimming | Non-dimming

White	MMP-060S/3H/W/1N/N.M/10A24.27.30.35.40/N1/2
Matte black	MMP-060S/3H/M/1N/N.M/10A24.27.30.35.40/N1/2
Chrome	MMP-060S/3H/S/1N/N.M/10A24.27.30.35.40/N1/2

Additional Accesaries

• Lens Filter

Full-Diffuser lens filter
MLA-060/DF01



Full-spread lens filter
MLA-060/SF01



Edge-control lens filter
MLA-060/EC01



Semi-Diffuser lens filter
MLA-060/DS01



Semi-Spread lens filter
MLA-060/SS01




Sharpen lens filter
MLA-060/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°




Medium : 19°




Light distribution with Filter lighting®


Full-Diffuser lens filter | MLA-060/DF01




Semi-Diffuser lens filter | MLA-060/DS01




Full-spread lens filter | MLA-060/SF01




Semi-Spread lens filter | MLA-060/SS01




Edge-control lens filter | MLA-060/EC01



Sharpen lens filter | MLA-060/SH01




The attachment of the filters



ACCENT | Track light


MMP-060S/SH



Products Specifications

- Input Voltage AC120V
- Power consumption 15.4W(AC120V)
- Luminance flux 941 ~ 1,088 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 0.84 lbs
- Light distribution Narrow (11°) Medium (19°)
- Input current 0.129A (120V)
- Aiming distance 0.1m (3 15/16 in)
- Tilting angle 100°
- Filter lighting® 2 Filters

Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA

NORDIC : type TEK-44,48,412
NORDIC ALUMINIUM INC

- This fixture is compatible with 2-circuit track only. The fixture attaches to both the left and right circuit rails of the track. Please ensure that only one power feed is supplied to the track.

Installation



Product code

[ex : Slant Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-060S/SH/W/1E/N/10A 30/Z1/ 2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 3-100%

White	MMP-060S/SH/W/1E/N.M/10A24.27.30.35.40/Z1/2
Matte black	MMP-060S/SH/M/1E/N.M/10A24.27.30.35.40/Z1/2
Chrome	MMP-060S/SH/S/1E/N.M/10A24.27.30.35.40/Z1/2

©NORDIC type

Dimming | Non-dimming

White	MMP-060S/SH/W/1N/N.M/10A24.27.30.35.40/N1/2
Matte black	MMP-060S/SH/M/1N/N.M/10A24.27.30.35.40/N1/2
Chrome	MMP-060S/SH/S/1N/N.M/10A24.27.30.35.40/N1/2

Additional Accesaries

• Lens Filter


Full-Diffuser lens filter
MLA-060/DF01



Semi-Diffuser lens filter
MLA-060/DS01



Full-spread lens filter
MLA-060/SF01



Semi-Spread lens filter
MLA-060/SS01



Edge-control lens filter
MLA-060/EC01




Sharpen lens filter
MLA-060/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°




Medium : 19°




Light distribution with Filter lighting®


Full-Diffuser lens filter | MLA-060/DF01




Semi-Diffuser lens filter | MLA-060/DS01




Full-spread lens filter | MLA-060/SF01




Semi-Spread lens filter | MLA-060/SS01




Edge-control lens filter | MLA-060/EC01



Sharpen lens filter | MLA-060/SH01



The attachment of the filters



AMBIENT | Ambient downlight


MMP-080F




Products Specifications

- Input Voltage AC120 ~ 277V
- Power consumption 29.0W(AC120V) / 30.3W(AC277V)
- Luminance flux 2,322 ~ 2,559 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 2.183 lbs
- Light distribution Flood (62°) Wide(42°) Medium (34°)
- Input current 0.7A
- Aiming distance 0.2m (7 7/8 in)
- Ceiling thickness 23/64~63/64 in
- Glare cut off angle 30°

Size



Installation



Product code

[ex : Chrome cone /White trim / Flood 62° / 3000K]

MMP-080F/CC/SWF/F/20B 30/Z1/ 2


Basic Product Series	Cone color	Trim color	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------------	------------	--------------------	--------------	-------------------	-------------	-------------------

©Round trim type
Dimming | 0-10V | 5-100%

White	MMP-080F/WC/SWF/F.W.M/ 20B27.30.35.40/Z1/2
Matte black	MMP-080F/MC/SWF.SMF/F.W.M/ 20B27.30.35.40/Z1/2
Chrome	MMP-080F/CC/SWF.SMF/F.W.M/ 20B27.30.35.40/Z1/2


Light distribution (for Chrome cone)

Flood : 62°




3000K / 2457Lm

Wide : 42°



3000K / 2457Lm

Medium : 34°



3000K / 2457Lm


MMP-080F




Products Specifications

- Input Voltage AC120 ~ 277V
- Power consumption 29.0W(AC120V) / 30.3W(AC277V)
- Luminance flux 2,322 ~ 2,559 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 2.183 lbs
- Light distribution Flood (62°) Wide(42°) Medium (34°)
- Input current 0.7A
- Aiming distance 0.2m (7 7/8 in)
- Ceiling thickness 23/64~63/64 in
- Glare cut off angle 30°

Size



Installation



Product code

[ex : Chrome cone /White trim / Flood 62° / 3000K]

MMP-080F/CC/CWF/F/20B 30/Z1/ 2


Basic Product Series	Cone color	Trim color	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------------	------------	--------------------	--------------	-------------------	-------------	-------------------

©Square trim type
Dimming | 0-10V | 5-100%

White	MMP-080F/WC/CWF/F.W.M/ 20B27.30.35.40/Z1/2
Matte black	MMP-080F/MC/CWF.CMF/F.W.M/ 20B27.30.35.40/Z1/2
Chrome	MMP-080F/CC/CWF.CMF/F.W.M/ 20B27.30.35.40/Z1/2


Light distribution (Chrome cone)

Flood : 62°




3000K / 2457Lm

Wide : 42°



3000K / 2457Lm

Medium : 34°



3000K / 2457Lm

WALL | Wall washer downlight

MMP-080W



Product code

[ex : Chrome cone /White trim / Wall washer / 3000K]

MMP-080W/CC/SWF/ 0 /20B 30/Z1/ 2

Basic Product Series	Cone color	Trim color	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------------	------------	--------------------	--------------	-------------------	-------------	-------------------


©Dimming | 0-10V | 10-100%

White	MMP-080W/WC/SWF/0/ 20B27.30.35.40/Z1/2
Matte black	MMP-080W/MC/SWF.SMF/0/ 20B27.30.35.40/Z1/2
Chrome	MMP-080W/CC/SWF.SMF/0/ 20B27.30.35.40/Z1/2


Products Specifications

- Input VoltageAC120 ~ 277V
- Power consumption30.1W(AC120V) / 31.6W(AC277V)
- Luminance flux2,211 ~ 2,479 lm
- Color renderingCRI (Ra)=93(typ)
- Fixture's weight2.39 lbs
- Light distributionWall washer
- Input current0.7A
- Aiming distance0.1m (3 15/16 in)
- Ceiling thickness23/64 ~ 63/64 in


Light distribution (Chrome cone)



Size



Installation



MMP-080A



Product code

[ex : Chrome cone /White trim / Narrow 12° / 3000K]

MMP-080A/CC/SWF/N/10B 30/Z1/ 2

Basic Product Series	Cone color	Trim color	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------------	------------	--------------------	--------------	-------------------	-------------	-------------------


©Dimming | 0-10V | 10-100%

White	MMP-080A/WC/SWF/N.M/ 10B27.30.35.40/Z1/2
Matte black	MMP-080A/MC/SWF.SMF/N.M/ 10B27.30.35.40/Z1/2
Chrome	MMP-080A/CC/SWF.SMF/N.M/ 10B27.30.35.40/Z1/2


Products Specifications

• Input Voltage	AC120 ~ 277V
• Power consumption	20.8W(AC120V) / 22.1W(AC277V)
• Luminance flux	1,685 ~ 1,857 lm
• Color rendering	CRI (Ra)=93(typ)
• Fixture's weight	2.34 lbs
• Light distribution	Narrow (12°) Medium (22°)
• Input current	0.5A
• Aiming distance	0.2m (7 7/8 in)
• Ceiling thickness	23/64 ~ 63/64 in
• Tilting angle	35°
• Filter lighting [®]	2 Filters

Size



Installation



Additional Accesaries

• Lens Filter


Full-Diffuser lens filter
MLA-080/DF01



Semi-Diffuser lens filter
MLA-080/DS03



Full-spread lens filter
MLA-080/SF01



Semi-Spread lens filter
MLA-080/SS01




Edge-control lens filter
MLA-080/EC02



Sharpener lens filter
MLA-080/SH01




How to do tilt lock




Light distribution (for Chrome cone)

Narrow : 12°



3000K / 1783Lm Solid line:vertically / Dotted line:tilt angel:25°


Medium : 22°



3000K / 1783Lm Solid line:vertically / Dotted line:tilt angel:25°


Light distribution (for Chrome cone) with Filter lighting[®]

Full-Diffuser lens filter | MLA-060/DF01




for Narrow Solid line:vertically / Dotted line:tilt angel:25° for Narrow 3000K / 1783Lm

Semi-Diffuser lens filter | MLA-060/DS01




for Narrow Solid line:vertically / Dotted line:tilt angel:25° for Narrow 3000K / 1783Lm

Full-spread lens filter | MLA-060/SF01




for Narrow Solid line:vertically / Dotted line:tilt angel:25° for Narrow 3000K / 1783Lm

Semi-Spread lens filter | MLA-060/SS01




for Narrow Solid line:vertically / Dotted line:tilt angel:25° for Narrow 3000K / 1783Lm

Edge-control lens filter | MLA-060/EC01




for Narrow Solid line:vertically / Dotted line:tilt angel:25° for Narrow 3000K / 1783Lm

Sharpener lens filter | MLA-060/SH01



for Narrow Solid line:vertically / Dotted line:tilt angel:25° for Narrow 3000K / 1783Lm

The attachment of the filters




MMP-080S/1H



Products Specifications

- Input Voltage AC120V
- Power consumption 21.8W(AC120V)
- Luminance flux 1,630 ~ 1,796 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 1.32 lbs
- Light distribution Narrow (11°) Medium (19°)
- Input current 0.183A (120V)
- Aiming distance 0.2m (7 7/8 in)
- Tilting angle 100°
- Filter lighting[®] 2 Filters

Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA

NORDIC : type TEK-44,48,412
NORDIC ALUMINIUM INC

- This fixture is compatible with 2-circuit track only. The fixture attaches to both the left and right circuit rails of the track. Please ensure that only one power feed is supplied to the track.

Installation



Product code

[ex : 10°Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-080S/1H/W/1E/N/10B 30/ Z2 /2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 3-100%

White	MMP-080S/1H/W/1E/N.M/10B27.30.35.40/Z2/2
Matte black	MMP-080S/1H/M/1E/N.M/10B27.30.35.40/Z2/2
Chrome	MMP-080S/1H/S/1E/N.M/10B27.30.35.40/Z2/2

©NORDIC type

Dimming | Non-dimming

White	MMP-080S/1H/W/1N/N.M/10B27.30.35.40/N1/2
Matte black	MMP-080S/1H/M/1N/N.M/10B27.30.35.40/N1/2
Chrome	MMP-080S/1H/S/1N/N.M/10B27.30.35.40/N1/2

Additional Accesaries

• Lens Filter


Full-Diffuser lens filter
MLA-080/DF01



Semi-Diffuser lens filter
MLA-080/DS03



Full-spread lens filter
MLA-080/SF01



Semi-Spread lens filter
MLA-080/SS01



Edge-control lens filter
MLA-080/EC02




Sharpeners lens filter
MLA-080/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°



Medium : 19°





Light distribution with Filter lighting[®]



Full-Diffuser lens filter | MLA-080/DF01



for Narrow





for Medium



Semi-Diffuser lens filter | MLA-080/DS03



for Narrow





for Medium



Full-spread lens filter | MLA-080/SF01



for Narrow





for Medium



Semi-Spread lens filter | MLA-080/SS01



for Narrow





for Medium



Edge-control lens filter | MLA-080/EC02



for Narrow




for Medium



Sharpeners lens filter | MLA-080/SH01



for Narrow



Narrow only

The attachment of the filters



- ① Remove the lock by sliding the body along the arrow direction, and detach the hood from the body.



- ② Rotate the option holder in the hood along the arrow direction and take the option holder out from the hood.




- ③ Put the filter into the hood.
※ up to 2 filters can be inserted.
※ The sharpeners lens are counted as 2 lens.



- ④ Put back the option holder to the hood.



- ⑤ Match the mark of the hood and the body and rotate the hood to lock.




MMP-080S/3H



Products Specifications

- Input Voltage AC120V
- Power consumption 21.8W(AC120V)
- Luminance flux 1,630 ~ 1,796 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 1.37 lbs
- Light distribution Narrow (11°) Medium (20°)
- Input current 0.183A (120V)
- Aiming distance 0.2m (7 7/8 in)
- Tilting angle 100°
- Filter lighting[®] 2 Filters

Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA

NORDIC : type TEK-44,48,412
NORDIC ALUMINIUM INC

- This fixture is compatible with 2-circuit track only. The fixture attaches to both the left and right circuit rails of the track. Please ensure that only one power feed is supplied to the track.

Installation



Product code

[ex : 30°Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-080S/3H/W/1E/N/10B 30/Z2 / 2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 3-100%

White	MMP-080S/3H/W/1E/N.M/10B27.30.35.40/Z2/2
Matte black	MMP-080S/3H/M/1E/N.M/10B27.30.35.40/Z2/2
Chrome	MMP-080S/3H/S/1E/N.M/10B27.30.35.40/Z2/2

©NORDIC type

Dimming | Non-dimming

White	MMP-080S/1H/W/1N/N.M/10B27.30.35.40/N1/2
Matte black	MMP-080S/1H/M/1N/N.M/10B27.30.35.40/N1/2
Chrome	MMP-080S/1H/S/1N/N.M/10B27.30.35.40/N1/2

Additional Accesaries

• Lens Filter


Full-Diffuser lens filter
MLA-080/DF01



Semi-Diffuser lens filter
MLA-080/DS03



Full-spread lens filter
MLA-080/SF01



Semi-Spread lens filter
MLA-080/SS01



Edge-control lens filter
MLA-080/EC02




Sharpeners lens filter
MLA-080/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°



Medium : 20°





Light distribution with Filter lighting[®]



Full-Diffuser lens filter | MLA-080/DF01



for Narrow





for Medium



Semi-Diffuser lens filter | MLA-080/DS03



for Narrow





for Medium



Full-spread lens filter | MLA-080/SF01



for Narrow





for Medium



Semi-Spread lens filter | MLA-080/SS01



for Narrow





for Medium



Edge-control lens filter | MLA-080/EC02




for Narrow




for Medium



Sharpeners lens filter | MLA-080/SH01



for Narrow



Narrow only

The attachment of the filters



① Remove the lock by sliding the body along the arrow direction, and detach the hood from the body.



② Rotate the option holder in the hood along the arrow direction and take the option holder out from the hood.




③ Put the filter into the hood.
※ up to 2 filters can be inserted.
※ The sharpeners lens are counted as 2 lens.



④ Put back the option holder to the hood.



⑤ Match the mark of the hood and the body and rotate the hood to lock.



Lock


MMP-080S/5H



Products Specifications

- Input Voltage AC120V
- Power consumption 21.8W(AC120V)
- Luminance flux 1,630 ~ 1,796 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 1.44 lbs
- Light distribution Narrow (11°) Medium (19°)
- Input current 0.183A (120V)
- Aiming distance 0.2m (7 7/8 in)
- Tilting angle 100°
- Filter lighting[®] 2 Filters

Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA

NORDIC : type TEK-44,48,412
NORDIC ALUMINIUM INC

• This fixture is compatible with 2-circuit track only.
The fixture attaches to both the left and right circuit rails of the track.
Please ensure that only one power feed is supplied to the track.

Installation



Product code

[ex : 50°Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-080S/5H/W/1E/N/10B 30/Z2 / 2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 3-100%

White	MMP-080S/5H/W/1E/N.M/10B27.30.35.40/Z2/2
Matte black	MMP-080S/5H/M/1E/N.M/10B27.30.35.40/Z2/2
Chrome	MMP-080S/5H/S/1E/N.M/10B27.30.35.40/Z2/2

©NORDIC type

Dimming | Non-dimming

White	MMP-080S/5H/W/1N/N.M/10B27.30.35.40/N1/2
Matte black	MMP-080S/5H/M/1N/N.M/10B27.30.35.40/N1/2
Chrome	MMP-080S/5H/S/1N/N.M/10B27.30.35.40/N1/2

Additional Accesaries

• Lens Filter


Full-Diffuser lens filter
MLA-080/DF01



Semi-Diffuser lens filter
MLA-080/DS03



Full-spread lens filter
MLA-080/SF01



Semi-Spread lens filter
MLA-080/SS01



Edge-control lens filter
MLA-080/EC02




Sharpen lens filter
MLA-080/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°



3000K / 1720Lm

Medium : 19°



3000K / 1720Lm


Light distribution with Filter lighting[®]




Full-Diffuser lens filter | MLA-080/DF01



for Narrow



for Narrow 3000K / 1720Lm




for Medium 3000K / 1720Lm




Semi-Diffuser lens filter | MLA-080/DS03



for Narrow



for Narrow 3000K / 1720Lm




for Medium 3000K / 1720Lm




Full-spread lens filter | MLA-080/SF01



for Narrow



for Narrow 3000K / 1720Lm




for Medium 3000K / 1720Lm




Semi-Spread lens filter | MLA-080/SS01



for Narrow



for Narrow 3000K / 1720Lm




for Medium 3000K / 1720Lm




Edge-control lens filter | MLA-080/EC02



for Narrow



for Narrow 3000K / 1720Lm




for Medium 3000K / 1720Lm



Sharpen lens filter | MLA-080/SH01



for Narrow



for Narrow 3000K / 1720Lm

Narrow only

The attachment of the filters



① Remove the lock by sliding the body along the arrow direction, and detach the hood from the body.



② Rotate the option holder in the hood along the arrow direction and take the option holder out from the hood.




③ Put the filter into the hood.
※ up to 2 filters can be inserted.
※ The sharpen lens are counted as 2 lens.



④ Put back the option holder to the hood.



⑤ Match the mark of the hood and the body and rotate the hood to lock.



Lock


MMP-080S/SH



Products Specifications

- Input Voltage AC120V
- Power consumption 21.8W(AC120V)
- Luminance flux 1,630 ~ 1,796 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 1.38 lbs
- Light distribution Narrow (11°) Medium (19°)
- Input current 0.183A (120V)
- Aiming distance 0.2m (7 7/8 in)
- Tilting angle 100°
- Filter lighting[®] 2 Filters

Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA

NORDIC : type TEK-44,48,412
NORDIC ALUMINIUM INC

- This fixture is compatible with 2-circuit track only.
The fixture attaches to both the left and right circuit rails of the track.
Please ensure that only one power feed is supplied to the track.

Installation



Product code

[ex : Slant Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-080S/SH/W/1E/N/10B 30/Z2 / 2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 10-100%

White	MMP-080S/SH/W/1E/N.M/10B27.30.35.40/Z2/2
Matte black	MMP-080S/SH/M/1E/N.M/10B27.30.35.40/Z2/2
Chrome	MMP-080S/SH/S/1E/N.M/10B27.30.35.40/Z2/2

©NORDIC type

Dimming | Non-dimming

White	MMP-080S/SH/W/1N.N.M/10B27.30.35.40/N1/2
Matte black	MMP-080S/SH/M/1N.N.M/10B27.30.35.40/N1/2
Chrome	MMP-080S/SH/S/1N.N.M/10B27.30.35.40/N1/2


Additional Accesaries

• Lens Filter

Full-Diffuser lens filter
MLA-080/DF01



Full-spread lens filter
MLA-080/SF01



Edge-control lens filter
MLA-080/EC02



Semi-Diffuser lens filter
MLA-080/DS03



Semi-Spread lens filter
MLA-080/SS01




Sharpeners lens filter
MLA-080/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°



3000K / 1720Lm

Medium : 19°



3000K / 1720Lm


Light distribution with Filter lighting[®]



Full-Diffuser lens filter | MLA-080/DF01



for Narrow




for Medium



Semi-Diffuser lens filter | MLA-080/DS03



for Narrow




for Medium



Full-spread lens filter | MLA-080/SF01



for Narrow




for Medium



Semi-Spread lens filter | MLA-080/SS01



for Narrow




for Medium



Edge-control lens filter | MLA-080/EC02



for Narrow




for Medium



Sharpeners lens filter | MLA-080/SH01



for Narrow



Narrow only

The attachment of the filters



① Remove the lock by sliding the body along the arrow direction, and detach the hood from the body.



② Rotate the option holder in the hood along the arrow direction and take the option holder out from the hood.




③ Put the filter into the hood.
※ up to 2 filters can be inserted.
※ The sharpeners lens are counted as 2 lens.



④ Put back the option holder to the hood.



⑤ Match the mark of the hood and the body and rotate the hood to lock.



AMBIENT | Ambient downlight

MMP-100F



Products Specifications

- Input Voltage

AC120 ~ 277V
- Power consumption

37.8W(AC120V) / 38.4W(AC277V)
- Luminance flux

3,317 ~ 3,649 lm
- Color rendering

CRI (Ra)=93(typ)
- Fixture's weight

5.5 lbs
- Light distribution

Flood (61°) Wide (47°)Medium (32°)
- Input current


0.9A
- Aiming distance

0.2m (7 7/8 in)
- Ceiling thickness


23/64 ~ 63/64 in
- Glare cut off angle

30°

Size



Installation



Product code

[ex : Chrome cone /White trim / Wide 47° / 3000K]

MMP-100F/CC/SWF/W/30B 30/Z1/ 2

Basic Product Series	Cone color	Trim color	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------------	------------	--------------------	--------------	-------------------	-------------	-------------------

©Dimming | 0-10V | 5-100%

White	MMP-100F/WC/SWF/F.W.M/30B27.30.35.40/Z1/2
Matte black	MMP-100F/MC/SWF.SMF/F.W.M/30B27.30.35.40/Z1/2
Chrome	MMP-100F/CC/SWF.SMF/F.W.M/30B27.30.35.40/Z1/2

Light distribution (Chrome cone)

Flood : 61°

F CC	61°	E(ft-cd)	2700K	3000K	3500K	4000K
H(ft) E(ft-cd) D(ft)						
3.28 226 3.90		3.28ft	214	226	231	236
6.56 56 7.81		6.56ft	54	56	58	59
9.84 25 11.71		9.84ft	24	25	26	26
13.12 14 15.62		13.12ft	13	14	14	15

3000K / 3500Lm

Wide : 47°

W CC	47°	E(ft-cd)	2700K	3000K	3500K	4000K
H(ft) E(ft-cd) D(ft)						
3.28 347 2.89		3.28ft	329	347	355	362
6.56 87 5.77		6.56ft	82	87	89	90
9.84 39 8.66		9.84ft	37	39	39	40
13.12 22 11.55		13.12ft	21	22	22	23

3000K / 3500Lm

Medium : 32°

M CC	32°	E(ft-cd)	2700K	3000K	3500K	4000K
H(ft) E(ft-cd) D(ft)						
3.28 587 1.94		3.28ft	556	587	600	612
6.56 147 3.87		6.56ft	139	147	150	153
9.84 65 5.81		9.84ft	62	65	67	68
13.12 37 7.74		13.12ft	35	37	37	38

3000K / 3500Lm

WALL | Wall washer downlight

U-B9451D



Products Specifications

- Input Voltage

AC120 ~ 277V
- Power consumption

1 : 0-10V) 30.5W(AC120V) / 31.4W(AC277V)
2 : Eco system) 30.8W(AC120V) / 30.8W(AC277V)
- Luminance flux

1935 ~ 2084 lm
- Color rendering

CRI (Ra)=93(typ)
- Fixture's weight

1 : 0-10V)5.6 lbs 2 : Eco system) 5.76 lbs
- Light distribution

Wall
- Input current


0.67A
- Aiming distance

0.2m (7 7/8 in)
- Ceiling thickness


23/64 ~ 63/64 in
- Glare cut off angle

35°

Size



Installation



Product code

[ex : White cone / White trim / 0-10V type / 3000K]

U - B 9 4 5 1 D / 1 / R 3 0 B / W C / W

Series	Fun-ction	Light source	Fun-ction	Auth-entification	Color temperature	Cone Color	Trim Color
--------	-----------	--------------	-----------	-------------------	-------------------	------------	------------


©Dimming | 0-10V | 5-100%

White	U-B9451D/1/R27B.R30B.R35B.R40B/WC/W(White)
Matte black	U-B9451D/1/R27B.R30B.R35B.R40B/MC/W(White).M(Matte black)
Chrome	U-B9451D/1/R27B.R30B.R35B.R40B/NC/W(White).M(Matte black)

©Dimming | Eco system | 3-100%

White	U-B9451D/2/R27B.R30B.R35B.R40B/WC/W(White)
Matte black	U-B9451D/2/R27B.R30B.R35B.R40B/MC/W(White).M(Matte black)
Chrome	U-B9451D/2/R27B.R30B.R35B.R40B/NC/W(White).M(Matte black)

Light distribution (Chrome cone)



NC / 3000K / 2018Lm

MMP-100A

C

UL

US



Products Specifications

- Input Voltage

AC120 ~ 277V
- Power consumption

36.4W(AC120V) / 36.8W(AC277V)
- Luminance flux

2,627 ~ 2,894 lm
- Color rendering

CRI (Ra)=93(typ)
- Fixture's weight

5.40 lbs
- Light distribution

Medium (20°) Narrow (12°)
- Input current

0.83A
- Aiming distance


0.3m (11 13/16 in)
- Ceiling thickness

23/64 ~ 63/64 in
- Tilting angle


35°
- Filter lighting®

2 Filters

Size



Installation



Product code

[ex : Chrome cone /White trim / Narrow 12° / 3000K]

MMP-100A/CC/SWF/N/30B 30/Z1/ 2

Basic Product Series	Cone color	Trim color	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------------	------------	--------------------	--------------	-------------------	-------------	-------------------

©Dimming | 0-10V | 5-100%


White	MMP-100A/WC/SWF/N.M/ 30B27.30.35.40/Z1/2
Matte black	MMP-100A/MC/SWF.SMF/N.M/ 30B27.30.35.40/Z1/2
Chrome	MMP-100A/CC/SWF.SMF/N.M/ 30B27.30.35.40/Z1/2

Additional Accesaries

• Lens Filter


Full-Diffuser lens filter MLA-100/DF01	Semi-Diffuser lens filter MLA-100/DS02
Full-spread lens filter MLA-100/SF01	Semi-Spread lens filter MLA-100/SS01
Edge-control lens filter MLA-100/EC02	Sharpener lens filter MLA-100/SH01

How to do tilt lock




Light distribution (for Chrome cone)


Narrow : 12°




Medium : 20°



Light distribution (for Chrome cone) with Filter lighting®



The attachment of the filters




MMP-100S/1H



Products Specifications

- Input Voltage AC120V
- Power consumption 39.9W(AC120V)
- Luminance flux 2,819 ~ 3,106lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 1.8 lbs
- Light distribution Narrow (11°) Medium (19°)
- Input current 0.334A (120V)
- Aiming distance 0. 3m (11 13/16in)
- Tilting angle 100°
- Filter lighting® 2 Filters

Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA
NORDIC : type TEK-44,48,412
NORDIC ALUMINIUM INC

• This fixture is compatible with 2-circuit track only.
The fixture attaches to both the left and right circuit rails of the track.
Please ensure that only one power feed is supplied to the track.

Installation



Product code

[ex : 10°Hood / White / EUTRACK type / Narrow 11° / 3000K]

MMP-100S/1H/W/1E/N/30B 30/Z2/ 2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 3-100%

White MMP-100S/1H/W/1E/N.M/30B27.30.35.40/Z2/2
Matte black MMP-100S/1H/M/1E/N.M/30B27.30.35.40/Z2/2
Chrome MMP-100S/1H/S/1E/N.M/30B27.30.35.40/Z2/2

©NORDIC type

Dimming | Non-dimming

White MMP-100S/1H/W/1N/N.M/30B27.30.35.40/N1/2
Matte black MMP-100S/1H/M/1N/N.M/30B27.30.35.40/N1/2
Chrome MMP-100S/1H/S/1N/N.M/30B27.30.35.40/N1/2


Additional Accesaries

• Lens Filter

Full-Diffuser lens filter
MLA-100/DF01



Full-spread lens filter
MLA-100/SF01



Edge-control lens filter
MLA-100/EC02



Semi-Diffuser lens filter
MLA-100/DS02



Semi-Spread lens filter
MLA-100/SS01




Sharpeners lens filter
MLA-100/SH01



How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.



Light distribution

Narrow : 11°

N	11°				
H(ft)	E(ft-cd)	D(ft)	2700K	3000K	3500K
3.28	2505	0.69	2819lm	2981lm	3045lm
6.56	626	1.38	2369	2505	2559
9.84	278	2.07	592	626	640
13.12	157	2.76	263	278	284
			148	157	160

3000K / 2981Lm

Medium : 19°

M	19°				
H(ft)	E(ft-cd)	D(ft)	2700K	3000K	3500K
3.28	1576	1.15	2819lm	2981lm	3045lm
6.56	394	2.30	1491	1576	1610
9.84	175	3.44	373	394	402
13.12	98	4.59	166	175	179
			93	98	101


3000K / 2981Lm

Light distribution


Full-Diffuser lens filter | MLA-100/DF01



for Narrow



for Medium 3000K / 2981Lm




for Medium 3000K / 2981Lm


Semi-Diffuser lens filter | MLA-100/DS02



for Narrow



for Medium 3000K / 2981Lm




for Medium 3000K / 2981Lm


Full-spread lens filter | MLA-100/SF01



for Narrow



for Medium 3000K / 2981Lm




for Medium 3000K / 2981Lm


Semi-Spread lens filter | MLA-100/SS01



for Narrow



for Medium 3000K / 2981Lm




for Medium 3000K / 2981Lm


Edge-control lens filter | MLA-100/EC02



for Narrow



for Medium 3000K / 2981Lm




for Medium 3000K / 2981Lm

Sharpeners lens filter | MLA-100/SH01



for Narrow



for Medium 3000K / 2981Lm

Narrow only

The attachment of the filters



① Remove the lock by sliding the body along the arrow direction, and detach the hood from the body.



② Rotate the option holder in the hood along the arrow direction and take the option holder out from the hood.




③ Put the filter into the hood.
※ up to 2 filters can be inserted.
※ The sharpeners lens are counted as 2 lens.




④ Put back the option holder to the hood.



⑤ Match the mark of the hood and the body and rotate the hood to lock.




MMP-100S/3H



Products Specifications

- Input Voltage AC120V
- Power consumption 39.9W(AC120V)
- Luminance flux 2,819 ~ 3,106 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 1.84 lbs
- Light distribution Narrow (11°) Medium (19°)
- Input current 0.334A (120V)
- Aiming distance 0. 3m (11 13/16 in)
- Tilting angle 100°
- Filter lighting® 2 Filters

Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA
NORDIC : type TEK-44,48,412
NORDIC ALUMINIUM INC

• This fixture is compatible with 2-circuit track only.
The fixture attaches to both the left and right circuit rails of the track.
Please ensure that only one power feed is supplied to the track.

Installation



Product code

[ex : 30°Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-100S/3H/W/1E/N/30B 30/Z2/ 2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 3-100%

White	MMP-100S/3H/W/1E/N.M/30B27.30.35.40/Z2/2
Matte black	MMP-100S/3H/M/1E/N.M/30B27.30.35.40/Z2/2
Chrome	MMP-100S/3H/S/1E/N.M/30B27.30.35.40/Z2/2

©NORDIC type

Dimming | Non-dimming

White	MMP-100S/3H/W/1N/N.M/30B27.30.35.40/N1/2
Matte black	MMP-100S/3H/M/1N/N.M/30B27.30.35.40/N1/2
Chrome	MMP-100S/3H/S/1N/N.M/30B27.30.35.40/N1/2


Additional Accesaries

• Lens Filter

Full-Diffuser lens filter
MLA-100/DF01



Full-spread lens filter
MLA-100/SF01



Edge-control lens filter
MLA-100/EC02



Semi-Diffuser lens filter
MLA-100/DS02



Semi-Spread lens filter
MLA-100/SS01




Sharpeners lens filter
MLA-100/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°



Medium : 19°




Light distribution




Full-Diffuser lens filter | MLA-100/DF01



for Narrow



for Narrow 3000K / 2981Lm




for Medium 3000K / 2981Lm




Semi-Diffuser lens filter | MLA-100/DS02



for Narrow



for Narrow 3000K / 2981Lm




for Medium 3000K / 2981Lm




Full-spread lens filter | MLA-100/SF01



for Narrow



for Narrow 3000K / 2981Lm




for Medium 3000K / 2981Lm




Semi-Spread lens filter | MLA-100/SS01



for Narrow



for Narrow 3000K / 2981Lm




for Medium 3000K / 2981Lm




Edge-control lens filter | MLA-100/EC02



for Narrow



for Narrow 3000K / 2981Lm




for Medium 3000K / 2981Lm



Sharpeners lens filter | MLA-100/SH01



for Narrow



for Narrow 3000K / 2981Lm

Narrow only

The attachment of the filters



① Remove the lock by sliding the body along the arrow direction, and detach the hood from the body.



② Rotate the option holder in the hood along the arrow direction and take the option holder out from the hood.




③ Put the filter into the hood.
※ up to 2 filters can be inserted.
※ The sharpeners lens are counted as 2 lens.



④ Put back the option holder to the hood.



⑤ Match the mark of the hood and the body and rotate the hood to lock.




MMP-100S/5H



Products Specifications

- Input Voltage AC120V
- Power consumption 39.9W(AC120V)
- Luminance flux 2,819 ~ 3,106 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 1.94 lbs
- Light distribution Narrow (11°) Medium (19°)
- Input current 0.334A (120V)
- Aiming distance 0. 3m (11 13/16 in)
- Tilting angle 100°
- Filter lighting® 2 Filters

Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA
NORDIC : type TEK-44,48,412
NORDIC ALUMINIUM INC

• This fixture is compatible with 2-circuit track only.
The fixture attaches to both the left and right circuit rails of the track.
Please ensure that only one power feed is supplied to the track.

Installation



Product code

[ex : 50°Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-100S/5H/W/1E/N/30B 30/Z2/ 2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 3-100%

White	MMP-100S/5H/W/1E/N.M/30B27.30.35.40/Z2/2
Matte black	MMP-100S/5H/M/1E/N.M/30B27.30.35.40/Z2/2
Chrome	MMP-100S/5H/S/1E/N.M/30B27.30.35.40/Z2/2

©NORDIC type

Dimming | Non-dimming

White	MMP-100S/5H/W/1N/N.M/30B27.30.35.40/N1/2
Matte black	MMP-100S/5H/M/1N/N.M/30B27.30.35.40/N1/2
Chrome	MMP-100S/5H/S/1N/N.M/30B27.30.35.40/N1/2


Additional Accesaries

• Lens Filter

Full-Diffuser lens filter
MLA-100/DF01



Full-spread lens filter
MLA-100/SF01



Edge-control lens filter
MLA-100/EC02



Semi-Diffuser lens filter
MLA-100/DS02



Semi-Spread lens filter
MLA-100/SS01




Sharpener lens filter
MLA-100/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°



3000K / 2981Lm


Medium : 19°



3000K / 2981Lm

Light distribution

Full-Diffuser lens filter | MLA-100/DF01




for Narrow

for Narrow 3000K / 2981Lm

for Medium 3000K / 2981Lm

Semi-Diffuser lens filter | MLA-100/DS02




for Narrow

for Narrow 3000K / 2981Lm

for Medium 3000K / 2981Lm

Full-spread lens filter | MLA-100/SF01




for Narrow

for Narrow 3000K / 2981Lm

for Medium 3000K / 2981Lm

Semi-Spread lens filter | MLA-100/SS01




for Narrow

for Narrow 3000K / 2981Lm

for Medium 3000K / 2981Lm

Edge-control lens filter | MLA-100/EC02




for Narrow

for Narrow 3000K / 2981Lm

for Medium 3000K / 2981Lm

Sharpener lens filter | MLA-100/SH01



for Narrow

for Narrow 3000K / 2981Lm

Narrow only

The attachment of the filters




- 1 Remove the lock by sliding the body along the arrow direction, and detach the hood from the body.
- 2 Rotate the option holder in the hood along the arrow direction and take the option holder out from the hood.
- 3 Put the filter into the hood.
※ up to 2 filters can be inserted.
※ The sharpener lens are counted as 2 lens.



- 4 Put back the option holder to the hood.
- 5 Match the mark of the hood and the body and rotate the hood to lock.


MMP-100S/SH



Products Specifications

- Input Voltage AC120V
- Power consumption 39.9W(AC120V)
- Luminance flux 2,819 ~ 3,106 lm
- Color rendering CRI (Ra)=93(typ)
- Fixture's weight 1.88 lbs
- Light distribution Narrow (11°) Medium (19°)
- Input current 0.334A (120V)
- Aiming distance 0. 3m (11 13/16 in)
- Tilting angle 100°
- Filter lighting® 2 Filters

Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA
NORDIC : type TEK-44,48,412
NORDIC ALUMINIUM INC

• This fixture is compatible with 2-circuit track only.
The fixture attaches to both the left and right circuit rails of the track.
Please ensure that only one power feed is supplied to the track.

Installation



Product code

[ex : Slant hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-100S/SH/W/1E/N/30B 30/Z2/ 2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 3-100%

White MMP-100S/SH/W/1E/N.M/30B27.30.35.40/Z2/2
Matte black MMP-100S/SH/M/1E/N.M/30B27.30.35.40/Z2/2
Chrome MMP-100S/SH/S/1E/N.M/30B27.30.35.40/Z2/2

©NORDIC type

Dimming | Non-dimming

White MMP-100S/SH/W/1N/N.M/30B27.30.35.40/N1/2
Matte black MMP-100S/SH/M/1N/N.M/30B27.30.35.40/N1/2
Chrome MMP-100S/SH/S/1N/N.M/30B27.30.35.40/N1/2


Additional Accesaries

• Lens Filter

Full-Diffuser lens filter
MLA-100/DF01



Full-spread lens filter
MLA-100/SF01



Edge-control lens filter
MLA-100/EC02



Semi-Diffuser lens filter
MLA-100/DS02



Semi-Spread lens filter
MLA-100/SS01




Sharpenr lens filter
MLA-100/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°




Medium : 20°




Light distribution


Full-Diffuser lens filter | MLA-100/DF01




Semi-Diffuser lens filter | MLA-100/DS02




Full-spread lens filter | MLA-100/SF01




Semi-Spread lens filter | MLA-100/SS01




Edge-control lens filter | MLA-100/EC02



Sharpenr lens filter | MLA-100/SH01



The attachment of the filters



MMP-130A

C

UL


US




Products Specifications

- Input VoltageAC120 ~ 277V
- Power consumption52.0W(AC120V) / 50.9W(AC277V)
- Luminance flux4,161 ~ 4,577 lm
- Color renderingCRI (Ra)=93(typ)
- Fixture's weight7.20 lbs
- Light distributionNarrow (11°) Medium (19°)
- Input current1.2A
- Aiming distance0.3m (11 13/16 in)
- Ceiling thickness23/64 ~ 63/64 in
- Tilting angle35°
- Filter lighting[®]2 Filters

Size



Installation



Product code

[ex : Chrome cone /White trim / Narrow 11° / 3000K]

MMP-130A/CC/SWF/N/40B 30/Z1/ 2

Basic Product Series	Cone color	Trim color	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------------	------------	--------------------	--------------	-------------------	-------------	-------------------

©Dimming | 0-10V | 10-100%

White	MMP-130A/WC/SWF/N.M/ 40B27.30.35.40/Z1/2
Matte black	MMP-130A/MC/SWF.SMF/N.M/ 40B27.30.35.40/Z1/2
Chrome	MMP-130A/CC/SWF.SMF/N.M/ 40B27.30.35.40/Z1/2

Additional Accesaries

• Lens Filter


Full-Diffuser lens filter
MLA-130/DF01



Semi-Diffuser lens filter
MLA-130/DS02



Full-spread lens filter
MLA-130/SF01



Semi-Spread lens filter
MLA-130/SS01




Edge-control lens filter
MLA-130/EC02



Sharpener lens filter
MLA-130/SH01




How to do tilt lock




Light distribution (for Chrome cone)

Narrow : 11°




Medium : 19°




Light distribution (for Chrome cone) with Filter lighting[®]


Full-Diffuser lens filter | MLA-130/DF01




Semi-Diffuser lens filter | MLA-130/DS02




Full-spread lens filter | MLA-130/SF01




Semi-Spread lens filter | MLA-130/SS01




Edge-control lens filter | MLA-130/EC02



Sharpener lens filter | MLA-130/SH01



The attachment of the filters




MMP-130S/1H



Products Specifications

- Input VoltageAC120V
- Power consumption52.0W(AC120V)
- Luminance flux4,161 ~ 4,577 lm
- Color renderingCRI (Ra)=93(typ)
- Fixture's weight3.38 lbs
- Light distributionNarrow (11°) Medium (18°)
- Input current0.441A (120V)
- Aiming distance0.3m (11 13/16 in)
- Tilting angle100°
- Filter lighting®2 Filters


Size




Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA

Installation



① Make sure ridge of adaptor aligns with groove in track.



② Turn knob A 90° clockwise to connect to track. the lighting rail.
③ Turn knob B 90° clockwise to connect to circuit 1.
and 90°anti-clockwise to connect to circuit 2.

Product code

[ex : 10°Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-130S/1H/W/2E/N/40B 30/ Z1 /2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 10-100%

White MMP-130S/1H/W/2E/N.M/40B27.30.35.40/Z1/2
Matte black MMP-130S/1H/M/2E/N.M/40B27.30.35.40/Z1/2
Chrome MMP-130S/1H/S/2E/N.M/40B27.30.35.40/Z1/2


Additional Accesaries

• Lens Filter

Full-Diffuser lens filter
MLA-130/DF01



Full-spread lens filter
MLA-130/SF01



Edge-control lens filter
MLA-130/EC02



Semi-Diffuser lens filter
MLA-130/DS02



Semi-Spread lens filter
MLA-130/SS01




Sharpener lens filter
MLA-130/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°




Medium : 18°




Light distribution with Filter lighting®


Full-Diffuser lens filter | MLA-130/DF01




Semi-Diffuser lens filter | MLA-130/DS02




Full-spread lens filter | MLA-130/SF01




Semi-Spread lens filter | MLA-130/SS01



Edge-control lens filter | MLA-130/EC02



Sharpener lens filter | MLA-130/SH01



The attachment of the filters

- ① Remove the lock by sliding the body along the arrow direction, and detach the hood from the body.
- ② Rotate the option holder in the hood along the arrow direction and take the option holder out from the hood.
- ③ Put the filter into the hood.
※ up to 2 filters can be inserted.
※ The sharpener lens are counted as 2 lens.

- ④ Put back the option holder to the hood.
- ⑤ Match the mark of the hood and the body and rotate the hood to lock.


MMP-130S/3H



Products Specifications

- Input VoltageAC120V
- Power consumption52.0W(AC120V)
- Luminance flux4,161 ~ 4,577 lm
- Color renderingCRI (Ra)=93(typ)
- Fixture's weight3.47 lbs
- Light distributionNarrow (11°) Medium (18°)
- Input current0.441A (120V)
- Aiming distance0.3m (11 13/16 in)
- Tilting angle100°
- Filter lighting®2 Filters


Size



Track system designation

EUTRAC : Series 230,233
EUTRAC CORP NA

Installation



- ① Make sure ridge of adaptor aligns with groove in track.
- ② Turn knob A 90° clockwise to connect to track. the lighting rail.
- ③ Turn knob B 90° clockwise to connect to circuit 1. and 90°anti-clockwise to connect to circuit 2.

Product code

[ex : 30°Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-130S/3H/W/2E/N/40B 30/ Z1 /2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 10-100%

White MMP-130S/3H/W/2E/N.M/40B27.30.35.40/Z1/2
Matte black MMP-130S/3H/M/2E/N.M/40B27.30.35.40/Z1/2
Chrome MMP-130S/3H/S/2E/N.M/40B27.30.35.40/Z1/2


Additional Accesaries

• Lens Filter

Full-Diffuser lens filter
MLA-130/DF01



Full-spread lens filter
MLA-130/SF01



Edge-control lens filter
MLA-130/EC02



Semi-Diffuser lens filter
MLA-130/DS02



Semi-Spread lens filter
MLA-130/SS01




Sharpener lens filter
MLA-130/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°




Medium : 18°




Light distribution with Filter lighting®


Full-Diffuser lens filter | MLA-130/DF01




Semi-Diffuser lens filter | MLA-130/DS02




Full-spread lens filter | MLA-130/SF01




Semi-Spread lens filter | MLA-130/SS01



Edge-control lens filter | MLA-130/EC02



Sharpener lens filter | MLA-130/SH01



The attachment of the filters

- ① Remove the lock by sliding the body along the arrow direction, and detach the hood from the body.
- ② Rotate the option holder in the hood along the arrow direction and take the option holder out from the hood.
- ③ Put the filter into the hood.
※ up to 2 filters can be inserted.
※ The sharpener lens are counted as 2 lens.

- ④ Put back the option holder to the hood.
- ⑤ Match the mark of the hood and the body and rotate the hood to lock.


MMP-130S/5H



Products Specifications


- Input VoltageAC120V
- Power consumption52.0W(AC120V)
- Luminance flux4,161 ~ 4,577 lm
- Color renderingCRI (Ra)=93(typ)
- Fixture's weight3.64 lbs
- Light distributionNarrow (11°) Medium (18°)
- Input current0.441A (120V)
- Aiming distance0.3m (11 13/16 in)
- Tilting angle100°
- Filter lighting®2 Filters

Size



Track system designation
EUTRAC : Series 230,233
EUTRAC CORP NA

Installation



Product code

[ex : 50°Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-130S/5H/W/2E/N/40B 30/ Z1 /2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 10-100%

White MMP-130S/5H/W/2E/N.M/40B27.30.35.40/Z1/2
Matte black MMP-130S/5H/M/2E/N.M/40B27.30.35.40/Z1/2
Chrome MMP-130S/5H/S/2E/N.M/40B27.30.35.40/Z1/2

Additional Accesaries

• Lens Filter

Full-Diffuser lens filter
MLA-130/DF01



Full-spread lens filter
MLA-130/SF01



Edge-control lens filter
MLA-130/EC02



Semi-Diffuser lens filter
MLA-130/DS02



Semi-Spread lens filter
MLA-130/SS01




Sharpener lens filter
MLA-130/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°




Medium : 18°




Light distribution with Filter lighting®


Full-Diffuser lens filter | MLA-130/DF01




Semi-Diffuser lens filter | MLA-130/DS02




Full-spread lens filter | MLA-130/SF01




Semi-Spread lens filter | MLA-130/SS01




Edge-control lens filter | MLA-130/EC02



Sharpener lens filter | MLA-130/SH01



The attachment of the filters



MMP-130S/SH



Products Specifications

- Input Voltage

AC120V
- Power consumption

52.0W(AC120V)
- Luminance flux

4,161 ~ 4,577 lm
- Color rendering

CRI (Ra)=93(typ)
- Fixture's weight

3.64 lbs
- Light distribution

Narrow (11°) Medium (19°)
- Input current


0.441A (120V)
- Aiming distance

0.3m (11 13/16in)
- Tilting angle

100°
- Filter lighting®

2 Filters

Size



Track system designation
EUTRAC : Series 230,233
EUTRAC CORP NA

Installation

- ①

① Make sure ridge of adaptor aligns with groove in track.
- ②

② Turn knob A 90° clockwise to connect to track. the lighting rail.
- ③

③ Turn knob B 90° clockwise to connect to circuit 1.
and 90° anti-clockwise to connect to circuit 2.

Product code

[ex : Slant Hood / White / EUTRAC type / Narrow 11° / 3000K]

MMP-130S/SH/W/2E/N/40B 30/ Z1 /2

Basic Product Series	Hood	Color	Track type	Light distribution	Light source	Color temperature	Driver type	Auth-entification
----------------------	------	-------	------------	--------------------	--------------	-------------------	-------------	-------------------

©EUTRAC type

Dimming | 0-10V | 10-100%

White MMP-130S/SH/W/2E/N.M/40B27.30.35.40/Z1/2
Matte black MMP-130S/SH/M/2E/N.M/40B27.30.35.40/Z1/2
Chrome MMP-130S/SH/S/2E/N.M/40B27.30.35.40/Z1/2

Additional Accesaries

• Lens Filter

Full-Diffuser lens filter
MLA-130/DF01



Full-spread lens filter
MLA-130/SF01



Edge-control lens filter
MLA-130/EC02



Semi-Diffuser lens filter
MLA-130/DS02



Semi-Spread lens filter
MLA-130/SS01




Sharpener lens filter
MLA-130/SH01




How to do tilt lock / pan lock

Each angle can be locked by allen wrench attached.




Light distribution

Narrow : 11°



Medium : 19°





Light distribution with Filter lighting®



Full-Diffuser lens filter | MLA-130/DF01



for Narrow





for Medium



Semi-Diffuser lens filter | MLA-130/DS02



for Narrow





for Medium



Full-spread lens filter | MLA-130/SF01



for Narrow





for Medium



Semi-Spread lens filter | MLA-130/SS01



for Narrow





for Medium



Edge-control lens filter | MLA-130/EC02



for Narrow




for Medium



Sharpener lens filter | MLA-130/SH01



for Narrow



Narrow only

The attachment of the filters



- ① Remove the lock by sliding the body along the arrow direction, and detach the hood from the body.



- ② Rotate the option holder in the hood along the arrow direction and take the option holder out from the hood.




- ③ Put the filter into the hood.
※ up to 2 filters can be inserted.
※ The sharpener lens are counted as 2 lens.



- ④ Put back the option holder to the hood.



- ⑤ Match the mark of the hood and the body and rotate the hood to lock.





ConsciLed


Linear Line light 【ConsciLed】

PAT.P / D.PAT.P in Japan



LED linear line light was developed by NANOTECO Corporation which the compound semiconductor research group at The University of Electro-Communications has established. The integration with the technologies originated from the academic field enhances this LED linear line light' s function and efficiency.

Specifications




Input Voltage	DC24V (dedicated driver)
Energy Consumption	12W (per 39 3/8")
Consumption Efficiency	98.6 lm/W
Weight	30g (per 39 3/8")
Maximum Length of Straight Line Connection	Max.314 61/64" ●Voltage drop prevention circuit included
Dustproof/Dripproof Performance	IP 65
Dimming Compatible	0-10V
Statement of Conformity/Standard	—
Product Warranty	Long-term 3 year warranty
Accessories	Mounting Clip (4pcs / per 39 3/8")

- The quantity of light per 39 3/8" is high such as maximum 1,234lm.
- Dimmable : 0-10V control type
- Long-term "3 year warranty"
- The width is only 7/16", so the installation in a limited space is possible.
- The voltage drop protection circuit is built in to prevent the nonuniformity of light.

Color Temperature | Light Source Luminous Flux (lm/W) | General Color Rendering Index (Ra)

Color Temperature (K)	Light Source Luminous Flux (lm/W)	General Color Rendering Index (Ra)
2400	1,187	83 typical
2700	1,169	93 typical
3000	1,191	93 typical
3500	1,217	93 typical
4000	1,234	93 typical

Light Distribution Data 3000K



Product Item Number

MAE-CL/B30/1000/Z1/2

Product Type length (mm) Color Temperature version

Sold Separately

 Fixed rail (mounting clip 4 pieces : supplied with the product) MAE-CRC04/1000/02	 Outer cover (Flat head) MAE-CFH/1024/01	 End cap (Flat head) MAE-CFE/01
 Fixed rail (mounting clip 12 pieces : supplied with the product) MAE-CRC12/1000/02	 Outer cover (Round head) MAE-CRH/1024/01	 End cap (Round head) MAE-CRE/01
 Mounting clip MAE-CCL/04/01	 Joint Spacer MAE-CJS/01	 Tilt bracket (4 pieces) MAE-CTB04/01

Product Item Number

Length	2400K	2700K	3000K	3500K	4000K
19 11/16" (500 mm)	MAE-CL/B24/0500/Z1/2	MAE-CL/B27/0500/Z1/2	MAE-CL/B30/0500/Z1/2	MAE-CL/B35/0500/Z1/2	MAE-CL/B40/0500/Z1/2
39 3/8" (1000 mm)	MAE-CL/B24/1000/Z1/2	MAE-CL/B27/1000/Z1/2	MAE-CL/B30/1000/Z1/2	MAE-CL/B35/1000/Z1/2	MAE-CL/B40/1000/Z1/2
59 1/16" (1500 mm)	MAE-CL/B24/1500/Z1/2	MAE-CL/B27/1500/Z1/2	MAE-CL/B30/1500/Z1/2	MAE-CL/B35/1500/Z1/2	MAE-CL/B40/1500/Z1/2
78 47/64" (2000 mm)	MAE-CL/B24/2000/Z1/2	MAE-CL/B27/2000/Z1/2	MAE-CL/B30/2000/Z1/2	MAE-CL/B35/2000/Z1/2	MAE-CL/B40/2000/Z1/2
98 27/64" (2500 mm)	MAE-CL/B24/2500/Z1/2	MAE-CL/B27/2500/Z1/2	MAE-CL/B30/2500/Z1/2	MAE-CL/B35/2500/Z1/2	MAE-CL/B40/2500/Z1/2
118 7/64" (3000 mm)	MAE-CL/B24/3000/Z1/2	MAE-CL/B27/3000/Z1/2	MAE-CL/B30/3000/Z1/2	MAE-CL/B35/3000/Z1/2	MAE-CL/B40/3000/Z1/2


● The length can be selected every 3 9/32" from 3 9/32" to 118 1/16" .

Specifications of Driver

Driver Number 96W : OT96W/24V/UNV/DIM


Driver size

OT96W/24V/UNV/DIM	
Input Voltage	120-277V 50/60Hz
DC Output	24V 4A
Power Factor	0.95
Max. Output Voltage	96W
Weight	453g
Dustproof/Dripproof Performance	IP64
Dimming Compatible	0-10V
Statement of Conformity/Standard	RoHS, RU, CSA



Installation Guide

[EXAMPLE] In case of connecting 78 47/64" of ConsciLed linear light to make 314 61/64" long



ModuleX Inc.

A ModuleX HOLDINGS Group Company

Head Office

#21 AraiBldg. 1-20-6 Ebisu-Minami Shibuya-ku, Tokyo, Japan
Tel : +81-3-3792-9111
Fax : +81-3-5768-3690



OSAKA branch

4-1-21 Kitahama, Chuo-ku, Osaka
Tel : +81-6-7167-2474
Fax : +81-6-7167-2477



FUKUOKA branch

1-8-30-1 Daimyo, Chuo-ku, Fukuoka, Japan
Tel : +81-92-732-4211
Fax : +81-92-732-4311



ModuleX LIGHTING SOLUTION CENTER Kanazawa

Mori Building 101,2-177, Irie, Kanazawa-shi, Ishikawa
Tel. +81-76-259-5620
Fax : +81-76-259-5621



ModuleX Factory

1-20-19 Horikiri, Katsushika-ku, Tokyo, Japan
Tel : +81-3-5672-7712
Fax : +81-3-5672-7736



SINGAPORE

ModuleX LIGHTING SOLUTIONS (SINGAPORE) Pte. Ltd.
18 Teck Lim Road, #01-01, Singapore 088390
Tel : +65 6221 5140



Sale Representative in North America

Mosheo Corp
2B Airport Drive Ext. Hopedale, MA 01747 U.S.A

London

CONCORD Lighting [Distributor]
Longbow House, 14-20 Chiswell Street, London, EC1Y 4TW, U.K.

Milan

ModuleX milan office
Via Gustavo Fara 10, 20124 Milan. ITALY.