### **FUNCTION**

### CAT.NO.

## MMP-100S/3H/1N/2

# **ModuleX°100**

# TRACK LIGHT



### **SPECIFICATION**

- Light Source
- Input Voltage
- Input current
- Power Consumption
- **Dedicated Driver**
- Weight
- **Dimming Control**
- Dimming Range
- UL File number

LED Module (Mounted.)

AC120V(Dedicated driver input voltage) 0.334A(AC120V input)

39.9W(AC120V input)

Constant current (50/60Hz shared)

1.84 lbs,835g (Driver weight is included)

E477257


- delivered lumen (N)for Narrow (M)for Medium
- life rating
- warranty coverage
- CRI(Ra)
- color temperature

41.1Lm/W(AC120V input) 49.0Lm/W(AC120V input) 50,000hours. L70

5 years 93 typ

2700K,3000K,3500K,4000K


### Narrow



2368	2504	2558	2609
592	626	640	652
263	278	284	290
148	156	160	163
	2819lm 2368 592 263	2819lm 2981lm 2368 2504 592 626 263 278	592 626 640 263 278 284

#### Medium 19° H(ft) E(ft-cd) D(ft) 3 28 1576 1.15 394 2.30 6 56 9.84 3.44 16964cd 13.12 98 4.59

3000K / 2981Lm



Set screw(M3)

# PRODUCT CODE

MMP-100S/3H/W or M or S/1N/N/30B27/N1/2 MMP-100S/3H/W or M or S/1N/N/30B30/N1/2 MMP-100S/3H/W or M or S/1N/N/30B35/N1/2 MMP-100S/3H/W or M or S/1N/N/30B40/N1/2 MMP-100S/3H/W or M or S/1N/M/30B27/N1/2 MMP-100S/3H/W or M or S/1N/M/30B30/N1/2 MMP-100S/3H/W or M or S/1N/M/30B35/N1/2 MMP-100S/3H/W or M or S/1N/M/30B40/N1/2

## HOW TO READ THE PRODUCT CODE

## MMP-100S/3H/W/1N/N/30B27/N1/2 2 3 4 5

- 1 Basic product Series
- 2 Hood type (3H)for 30° hood
- Choose the letter code to designate the desired color of Product (W)for White (M)for Matte Black (S)for Silver
- Adapter Type (1N) for NORDIC ALUMINIUM INC
- 5 Choose the letter code to designate the desired light distribution (N)for Narrow 11° (M)for Medium 19°
- 6 Light Source
- Choose the letter code to designate the desired Color Temperature (27) for 2700K (30) for 3000K (35) for 3500K (40) for 4000K
- Designates led driver type (N1)for Non-Dimming
- 9 Authentication (2)for UL/cUL

## Lens Filter options

Full-Diffuser Lens Filter MI A-100/DF01 MLA-100/DS02 Semi-Diffuser Lens Filter Full-Spread Lens Filter MLA-100/SF01 Semi-Spread Lens Filter MLA-100/SS01 MLA-100/EC02 Edge Control Lens Filter Sharpener Lens MLA-100/SH01 (available only for narrow distribution)

# 7 3/64" 35mm 179mm 124.4mm 4 57/64 Pan lock Set screw(M3) 71.5mm 2 13/16" 3 57/64 2 13/16"


### ATTENTION


53.1mm

35.8mm

•This fixture is compatible with NORDIC ALUMINIUM 2-circuit track only. The fixture attaches to both the left and right circuit rails of the track. Please ensure that only one power feed is supplied to the track.

99.0mm





71.5mm

ModuleX Inc

**SPECIFICATION SHEET** 

CREATED DATE 6/29/2018 **REVISION DATE** 7/27/2018