


SPECIFICATION

- Light Source
- Input Voltage
- Input current
- Power Consumption
- Dedicated Driver
- Weight
- Dimming Control
- Dimming Range
- UL File number

LED Module (Mounted)  
 AC120V(Dedicated driver input voltage)  
 0.334A(AC120V input)  
 39.9W(AC120V input)  
 Constant current ( 50/60Hz shared)  
 1.94 lbs,880g (Driver weight is included)  
 -  
 -  
 E477257


- delivered lumen (N)for Narrow (M)for Medium
  - life rating
  - warranty coverage
  - CRI(Ra)
  - color temperature
- 33.8Lm/W(AC120V input)  
 42.0Lm/W(AC120V input)  
 50,000hours. L70  
 5 years  
 93 typ  
 2700K,3000K,3500K,4000K

**Narrow**



E(ft-cd)	2700K	3000K	3500K	4000K
2819lm	2981lm	3045lm	3106lm	
3.28ft	2368	2504	2558	2609
6.56ft	592	626	640	652
9.84ft	263	278	284	290
13.12ft	148	156	160	163

**Medium**



E(ft-cd)	2700K	3000K	3500K	4000K
2819lm	2981lm	3045lm	3106lm	
3.28ft	1490	1576	1610	1642
6.56ft	373	394	402	411
9.84ft	166	175	179	182
13.12ft	93	98	101	103

**PRODUCT CODE**

- MMP-100S/5H/W or M or S/1N/N/30B27/N1/2
- MMP-100S/5H/W or M or S/1N/N/30B30/N1/2
- MMP-100S/5H/W or M or S/1N/N/30B35/N1/2
- MMP-100S/5H/W or M or S/1N/N/30B40/N1/2
- MMP-100S/5H/W or M or S/1N/M/30B27/N1/2
- MMP-100S/5H/W or M or S/1N/M/30B30/N1/2
- MMP-100S/5H/W or M or S/1N/M/30B35/N1/2
- MMP-100S/5H/W or M or S/1N/M/30B40/N1/2


**HOW TO READ THE PRODUCT CODE**

MMP-100S/5H/W/1N/N/30B27/N1/2  
 1 2 3 4 5 6 7 8 9

- Basic product Series
- Hood type (5H)for 50° hood
- Choose the letter code to designate the desired color of Product (W)for White (M)for Matte Black (S)for Silver
- Adapter Type (1N)for NORDIC ALUMINIUM INC
- Choose the letter code to designate the desired light distribution (N)for Narrow 11° (M)for Medium 19°
- Light Source
- Choose the letter code to designate the desired Color Temperature (27)for 2700K (30)for 3000K (35)for 3500K (40)for 4000K
- Designates led driver type (N1)for Non-Dimming
- Authentication (2)for UL/cUL

**Lens Filter options**

- Full-Diffuser Lens Filter MLA-100/DF01
- Semi-Diffuser Lens Filter MLA-100/DS02
- Full-Spread Lens Filter MLA-100/SF01
- Semi-Spread Lens Filter MLA-100/SS01
- Edge Control Lens Filter MLA-100/EC02
- Sharpener Lens MLA-100/SH01 (available only for narrow distribution)



**ATTENTION**

• This fixture is compatible with NORDIC ALUMINIUM 2-circuit track only. The fixture attaches to both the left and right circuit rails of the track. Please ensure that only one power feed is supplied to the track.

