



SPECIFICATION

- | | | |
|---|--|---|
| <ul style="list-style-type: none"> ● Light Source ● Input Voltage ● Input current(1) ● Input current(2) ● Power Consumption(1) ● Power Consumption(2) ● Dedicated Driver ● Fixture Input Voltage ● Fixture Input Current ● Weight ● Dimming Control ● Dimming Range | <p>LED Module (Mounted)
 AC120-277V(Dedicated driver input voltage)
 0.255A(AC120V input),0.121A(AC277V input)
 0.259A(AC120V input),0.116A(AC277V input)
 30.5W(AC120V input),31.4W(AC277V input)
 30.8W(AC120V input),30.8W(AC277V input)
 Constant current (50/60Hz shared)
 38.4V
 0.67A
 (1)5.6 lbs,2.54kg (2)5.76lbs,2.61kg
 (1)0-10V (2)EcoSystem
 (1)5%-100% (2)3%-100%</p> | <ul style="list-style-type: none"> ● UL File number ● delivered lumen ● life rating ● warranty coverage ● CRI(Ra) ● color temperature <p>E472786
 15.9Lm/W(AC120V input),15.4Lm/W(AC277V input)
 50,000hours. L70
 5 years
 93 typ
 2700K,3000K,3500K,4000K</p> |
|---|--|---|

Solid line:Wall/Vertically
Dotted line:Wall/Horizontally



NC / 3000K / 2018Lm



PRODUCT CODE

- U-B9451D/1/R27B/WC/W
- U-B9451D/1/R27B/MC/W or M
- U-B9451D/1/R27B/NC/W or M
- U-B9451D/1/R30B/WC/W
- U-B9451D/1/R30B/MC/W or M
- U-B9451D/1/R30B/NC/W or M
- U-B9451D/1/R35B/WC/W
- U-B9451D/1/R35B/MC/W or M
- U-B9451D/1/R35B/NC/W or M
- U-B9451D/1/R40B/WC/W
- U-B9451D/1/R40B/MC/W or M
- U-B9451D/1/R40B/NC/W or M

HOW TO READ THE PRODUCT CODE

U-B9451D/1/R30B/WC/W
 1 2 3 4 5

- 1 Basic product Series
- 2 Designates led driver type
(1)for OSRAM,Cat No. OT40W/PRG1400C/UNV/DIM-1
(2)for LUTRON,Cat No. LDE14U1UKN-BA067
- 3 Choose the letter code to designate the desired Color Temperature
(27)for 27000K (30)for 3000K (35)for 3500K (40)for 4000K
- 4 Choose the letter code to designate the desired color of cone
(WC)for White cone (MC)for Matte black cone (NC)for Natural cone
- 5 Choose the letter code to designate the desired color of Trim
(W)for White (M)for Matte black

